

DIRECTIONS FOR USE

Prepare the surface free from grease and dirt by washing with weak solution of washing soda. Then rinse with clear water. Wax can be removed with turpentine or benzine.

The more care used in preparing the surface, the better the finish will be.

For touch-up work, or where the desire is to bring out the original beauty of the wood, apply a coat of the stain just as received. If the surface has been badly scratched, two coats should be applied to bring out a deep and better lustre.

If a light colored stain is desired, and the surface is dark, a coat of Integrity Ground Color should first be applied.

New floors and woodwork of open grained wood, such as ash, chestnut, oak, mahogany and walnut should first be filled with a paste wood filler. Close-grained woods do not require filling.



EASY
BRUSHING

QUICK
DRYING

Integrity

MADE TO ENDURE

VARNISH STAINS

for Floors, Furniture and Woodwork



INTEGRITY PAINT CO.

NEW HAVEN

NEW YORK

Integrity

VARNISH STAINS

INTEGRITY Varnish Stains are designed to impart beauty and durability to floors, furniture and woodwork. They are composed of a high-grade, tough, waterproof varnish, and the best stain materials. Varnish and stain in one operation, giving correct imitations of hardwood finishes. Dry hard overnight, and are suitable for both exterior and interior use. These stains will stand the hardest kind of wear and tear.



175—LIGHT OAK




176—DARK OAK



177—CHERRY



178—MAHOGANY



179—WALNUT



180—GROUND COLOR

Y T Z 1310205965